

TRACTION CLEAN

Slip Resistant Cleaner/Degreaser

Traction Clean is formulated to provide the cleaning and soil suspension properties necessary to effectively clean and maintain positive slip resistant characteristics in restaurant and food service areas, restrooms, nursing homes, hospitals, and light industrial manufacturing facilities where food, protein-based soils, light oils, and dirt can cause slippery conditions. Detergents and surfactants effectively break down and suspend soils, removing the potential cause of many slippery floors. Special additives increase the coefficient of friction beyond the level normally inherent in the existing floor surface. Extensive laboratory and field testing on various types of flooring (including resilient tile, ceramic and stone tile, sealed wood, and concrete) has demonstrated this product's ability to raise the coefficient of friction readings beyond those required by the Occupational Safety and Health Administration and the 0.6 SCOF recommended by the National Floor Safety Institute, ANSI and Americans With Disabilities Act.



APPLICATION & MAINTENANCE

Dilute Traction Clean with warm water at the following dilutions, depending on the degree and type of soil to be removed:

Light Duty Cleaning: 8 ounces Traction Clean per gallon of water (1:16).

Medium Duty Cleaning: 12 ounces Traction Clean per gallon of water (1:10).

Heavy Duty Cleaning: 16 ounces Traction Clean per gallon of water (1:8).

Apply with either an autoscrubber or by damp mopping. In order to avoid redepositing grease and protein soils when damp mopping, a two bucket system in which one bucket contains the Traction Clean and one bucket is used for soiled solution, should be used. Heavy deposits of protein soil, dirt or grease may be addressed by applying Traction Clean at 16 ounces per gallon using a pressurized sprayer, watering can, or mop. Scrub the area with a stiff bristled brush or buffing machine, remove the soiled solution with a wet vacuum or mop, and finish the cleaning procedure by damp mopping. Allow the floor to dry. Do not rinse.

SPECIFICATIONS

Active Ingredients	Synthetic and Alkaline Detergents, Slip Resistant
pH	11.0-12.0
Free Ammonia	None
Free Alkali	None
Free Acid	None
Phosphates	None
Abrasives	None
Color	Blue
Odor	Moderate
Solubility in Water	Complete
Freeze/Thaw Stability	3 cycles
Shelf Life	1 year minimum at room temp.
Flash Point	>200°F
Weight Per Gallon	8.5 lbs
Biodegradable	Yes
Soil Suspension	Excellent

SAFETY INFORMATION

Health	2
Flammability	0
Reactivity	0
Personal Protection	B

CAUTION: Contains alkaline detergents. May cause irritation in undiluted concentrations. If ingested, give vinegar, lemon or orange juice. Follow with olive oil. For external contact, flood with water. In the event of eye contact, flush with plenty of clean water. **Contact a physician immediately.** Contains 2-Butoxyethanol CAS# 111-76-2, and 2-Amino Ethanol CAS# 141-43-5. Read MSDS thoroughly before using.



605 Springs Road, Bedford, MA 01730 USA
Tel: 978.667.5161, Fax: 978.670.5797
E-mail: Info@perma.com
www.perma.com