

STRONG HOLD

Acrylic/Urethane Concrete Sealer/Conditioner

Strong Hold concrete sealer/conditioner has been formulated to penetrate concrete surfaces and place a protective, chemical resistant acrylic/urethane matrix within the top layer of concrete surfaces that prevents staining and spotting from engine oil, brake fluid, transmission fluid, hydraulic oils, grease, etc. The treated surface is left clear, glossy, and easier to clean.



APPLICATION & MAINTENANCE

1. Remove any coatings and other foreign matter from surface. Use a high quality degreaser such as Perma #156 Deep Impact or #150 Grease Cutter applied through a pressure washer or automatic scrubber to remove heavy dirt, oil, and grease stains. Use a high quality all purpose cleaner such as Perma #129 Super Blue or #180 Geo-Clean, to clean light soil from a new installation. Follow directions on label; make sure surface is clean and dry before applying Strong Hold Concrete Sealer/Conditioner to avoid sealing in dirt and residue.
2. Strong Hold Concrete Sealer/Conditioner can be applied with a lambs wool applicator or paint roller. Avoid puddling, foaming and uneven application. Make sure to roll out any foam created by paint roller application.
3. Generally, one coat is sufficient to achieve effective impregnation/sealing of most concrete surfaces. Use visual judgement in determining whether a second coat of Strong Hold is necessary to achieve desired penetration and sealing of the concrete.
4. Depending on temperature and humidity conditions, treated areas should be dry enough to open to traffic in 3-5 hours.

STORAGE: 12 month shelf life. Keep container closed when not in use. Store upright at room temperature 65-70°F.

SPECIFICATIONS

Color	Clear, Light Amber
Solids	32%
Weight Per Gallon	7.2
Viscosity	20 Cps
Solvents	Mineral Spirits
Flash Point	105°F minimum
Dry Time	20 minutes
Water Resistant	24 hours-No effect
Alcohol	1 hour-No effect
Gasoline	1 hour-No effect
Caustic 5%	24 hours-No effect
Soap Resistance	2 hours-No effect
Slip Resistance	> 0.6
Coverage	500-750Ft.2/Gallon
VOC	<600 grams/liter

SAFETY INFORMATION

Health	1
Flammability	2
Reactivity	0
Personal Protection	B

DANGER: Harmful or Fatal if Swallowed. Contains Stoddard Solvent CAS#8052-41-3. Do Not Induce Vomiting. Call Physician Immediately.

COMBUSTIBLE: Flash Point 105°F. Keep away from heat and open flame. Close container after each use. Provide adequate ventilation. Read Material Safety Data Sheet thoroughly before using.



605 Springs Road, Bedford, MA 01730 USA
Tel: 978.667.5161, Fax: 978.670.5797
E-mail: Info@perma.com
www.perma.com