

ONE STEP

Low Speed Spray Buff Gloss Restorer

Perma's labor saving One Step Spray Buff is designed for use with 175-300 rpm buffing machines. This spray buff cleans and restores floors to a high gloss, reducing the need for more expensive, time-consuming stripping and recoating. Formulated with acrylic co-polymers and cleaning agents, this spray buff produces a clean, slip resistant glossy finish on all resilient and composition floors without powdering.

Routine use removes black heel marks, scuff marks and dirt, while exhibiting minimal build up. It can be easily removed with any quality stripping solution.



APPLICATION & MAINTENANCE

Sweep or dry mop floors to remove loose dirt and soil prior to spray buffing. Washing with Tops Neutral Cleaner may be required under heavier soil conditions. Fill a mechanical or hand-operated sprayer with spray buff. Apply the spray buff in a fine mist over a 4' X 8' area, and then buff dry with a buffing pad or brush. Unused spray buff should not be returned to the original container. For optimum gloss retention, floors should be cleaned with a clean dry mop or a dry mop treated with Aqua Treat, a water-based mop treatment, on a daily basis.

SPECIFICATIONS

Nonvolatile Solids	5 ± 0.5%
Total Active	9.2%
pH	8.0 - 8.8
Gloss 60°	82
Color	Pink
Weight Per Gallon	8.4 - 8.5
Slip Resistance (ASTM)	0.55 minimum
Stability	1 year minimum at room temperature
Freeze/Thaw Stability	3 cycles minimum
Drying Time	5 - 10 minutes
Water Resistance	Excellent
Gallon Coverage (Feet ²)	2000 ± 10%
Removability (Gardner)	75 cycles maximum

SAFETY INFORMATION

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

This material is not a hazardous mixture as defined in 29 CFR 1919, 1200, and M.G.L. c. 111F. Safety glasses and gloves should be worn during application and handling. If ingested, drink milk, water, or fruit juice and induce vomiting with oil of ipecac. In the event of eye contact, flush area with water for 15 minutes. **Consult with a physician.** Read Material Safety Data Sheet thoroughly before using.



605 Springs Road, Bedford, MA 01730 USA
Tel: 978.667.5161, Fax: 978.670.5797
E-mail: Info@perma.com
www.perma.com